



EUCON RETARDER 100

WATER REDUCING - EXTENDED SET CONTROLLING RETARDER

EUCLID CHEMICAL

DESCRIPTION

EUCON RETARDER 100 is a synthetically produced liquid water-reducing and set retarding admixture for concrete. It is a modified sodium gluconate. EUCON Retarder 100 does not contain calcium chloride or other potential corroding materials and may be used in the presence of aluminum or zinc embedments. EUCON Retarder 100 may be used at varying dosage rates to achieve extended set times compared to a control mix of up to 30 hours. It is compatible with air-entraining agents, water reducers and calcium chloride.

PRIMARY APPLICATIONS

- Prestressed concrete
- Concrete requiring water reduction and set time control
- Architectural concrete
- Hot weather concrete placement

FEATURES/BENEFITS

Plastic Concrete

- Retards setting characteristics
- Improves finishability
- Improves workability
- Reduces water requirements
- Reduces segregation

Hardened Concrete



- Increases strengths
- Improves finished appearance
- Reduces cracking
- Reduces permeability
- Non staining

TECHNICAL INFORMATION

Performance Data

The following test results were achieved using typical ASTM C 494 mix design requirements, 517 lb/yd³ (307 kg/m³) cement content and similar (± 0.5)% air content.

These results were obtained under laboratory conditions with materials and mix designs meeting the specifications of ASTM C 494. Changes in materials and mix designs can affect the dosage response of EUCON RETARDER 100.



PACKAGING

EUCON RETARDER 100 is packaged in bulk, 275 gal (1041 L) totes, 55 gal (208 L) drums or 5 gal (18.9 L) pails.

SHELF LIFE

1 year in original, unopened package.

SPECIFICATIONS/COMPLIANCES

EUCON RETARDER 100 meets or exceeds the requirements of:

- ASTM C 494, Type B & D
- AASHTO M 194
- CSA Standard CAN3 A266.2-M78

DIRECTIONS FOR USE

EUCON RETARDER 100 is normally used at dosages of 2 to 6 oz per 100 lb (130 to 390 ml per 100 kg) of cementitious material, depending on the application. Higher dosages are acceptable with prior testing and confirmation of the desired performance with specific materials being used.

EUCON RETARDER 100 should be added to the initial batch water of the concrete mixture. Do not dispense onto dry cement.

PRECAUTIONS/LIMITATIONS

- Care should be taken to maintain EUCON RETARDER 100 above freezing; however, freezing and subsequent thawing will not harm the material if thoroughly agitated.
- Add to mix independent of other admixtures.
- In all cases, consult the Safety Data Sheet before use.

Rev. 11.14

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.